



APPROVED MATERIALS LIST (WATER)

Material	Accepted Manufacturer		
PVC Pipe - SDR-21 for 3" and smaller C-900 DR14 for 4" and 6"	Diamond JM Eagle	Vulcan NAPCO	National Westlake
Ductile Iron Pipe - Class 51 or 350 Pressure (All pipe larger than 6" <u>must</u> be DIP)	U.S. Pipe McWane Ductile	American	
Service Line (Domestic only, Endopure ¾" 250 PSI IPS Blue SDR7 Polyethylene Pipe)	Endot		
Valves (Valves 3" and up to be mechanical joint only)	Mueller A-2361 RWGV w/ Aquagrip or MJ Fitting		
Tapping Valves	Mueller T-2362		
Threaded Valves	Mueller A-2380-8 (2" For Blow-Off Valves Only)		
Tapping Sleeves for Ductile Iron & Cast Iron	Mueller H-615 Romac SST	Ford Fast SST American Flow Control Series 2800	
Tapping Sleeves for PVC	Romac SST Ford Fast		
Ductile Iron Fittings	Tyler Union Star (MJ Accessory Kits – Tyler Union, Star, Romac, Global Industrial Components Domestic only)		
Mechanical Joint Restraint (Compatible to AWWA C153 or C110 MJ Fittings)	EBAA Iron (1100 Megalug) StarGrip (Series 3000)	EBAA Iron 2000PV Series Romac (Roma Grip)	
Push On Pipe Joint Restraint (Compatible to AWWA C151 ductile iron pipe)	U.S. Pipe (TR Flex or Field Lok 350 Gasket) American (Flex Ring) McWane Ductile (Sure Stop 350 Gasket)		
Stainless Steel & Brass Fittings	Domestic Only		
Hydrants	Mueller Centurion 250		
Stub out Materials	Saddle (Ford S70, S90 (C900), Mueller S-1300 Series, AY McDonald 3895) Saddle (Mueller, DR 2A Series (Ductile) Romac 202U) Corporation (Mueller H-15008/Ford 100-3-Q) Curb Stop (Mueller B20200R, Mueller B-25172N, Ford B11-233, Ford B41-233-W-Q-DL ¾")		
Valve Boxes	461S		

All piping, including valves and fittings, shall be of the type and size as shown on the *approved* drawings and in accordance with the Standard Specifications. All material shall be certified for use for potable water under ANSI/NSF Standard 61.